

Low- Drift Star Ratings *** 3-Star Rating ** 2-Star Rating * 1-Star Rating

Spray Tip	Capacity Size	Material			Bar												
		VP	VS	VK	1,0	1,5	2,0	2,5	3,0	3,5	4,0	4,5	5,0	5,5	6,0	6,5	7,0
TT	11004					**	**										
	11005				***	**	**	**	**								
TTJ60	11025					**	**	** to 2.75									
	11003					**	**	**									
	11004					**	**	** to 2.75									
	11005					**	**	**	** to 3.25								
AIXR	110025				*** to 1.4	**	**	**	**	**	**	**	**	**			
	11003				*** to 1.4	**	**	**	**	**	**	**	**	**			
	11004				***	*** to 1.7	**	**	**	**	**	**	**	**			
	11005				***	***	***	*** to 2.9	**	**	**	**	**	**			
	11006				***	***	***	***	***	*** to 3.9	**	**	**				
	11002					**	**										
AI3070	11002					**	**										
	110025					**	**	**	**								
	11003					**	**	**	**								
	11004					***	***	**	**	**	**	**	**	**			
	11005					***	***	***	***	***	***	**	**	**	**	**	**
	11002					***	*** to 2.25	**	**	**	**	**					
AITTJ60	110025					***	***	***	**	**	**	**					
	11003					***	***	**	**	**	**	**					
	11004					***	***	***	***	***	**	**	**	**			
	11005					***	***	***	***	***	***	***	***	***			
	11002						***		**								
AIC	110025						***		**								
	11003						***		**	**	**	**	**				
	11004						***		**	**	**	**	**				
	11005						***		**	**	**	**	**				
	11002						***		**								
AIC-VP	110025						***		**								
	11003						***		**	**	**	**	**				
	11004						***		**	**	**	**	**				
	11005						***		**	**	**	**	**				
	11002						***	***	***	**	**						
AI	110025				***	***	***		**	**	**						
	11003						***	***	***		**	**	**	**	**		
	11004						***	***	***		**	**	**	**	**		
	11005						***	***	***		**		***		**		
	11002						***	***	***	***	*** to 4.25	**	**				
TTI60	110025					***	***	***	***	***	***	***	***				
	11003					***	***	***	***	***	***	***	***				
	11004					***	***	***	***	***	***	***	***				
	11005					***	***	***	***	***	***	***	***				
	11002				***	***	***	***	***	***	***	***	***	***	**	**	**
TTI	110025				***	***	***	***	***	***	***	***	***	***	**	**	**
	11003				***	***	***	***	***	***	***	***	***	***	**	**	**
	11004				***	***	***	***	***	***	***	***	***	***	***	***	***
	11005				***	***	***	***	***	***	***	***	***	***	***	***	***
	11006				***	***	***	***	***	***	***	***	***	***	**	**	**

Materials: VP (POM) - VS (Stainless Steel) - VK (Ceramic)

Nozzle Spacing: 50cm above target surface not more than 2m above the ground surface if crop continues into buffer zone or not more than 1 m above ground surface if no crop in buffer zone or vegetation of at least the same height as the crop being treated.

